

Courtfalt®

Technical data sheet

Courtfalt® is a 6mm free-draining asphalt product designed specifically for tennis courts.

A 6mm free-draining open graded asphalt concrete (AC), is mixed using 100/150 pen grade bitumen. The product must be laid on a porous base layer.

Installation must be carried out by a competent sports surfacing specialist contractor on free-draining base layers.

The surface should be kept as clean as practicable. Brush or vacuum any leaves, spillages / site detritus. Power washers are not recommended as contaminants can be forced into the matrix and cause blockages lower down in the construction.

Courtfalt Binder Course

Offers the same characteristics as Courtfalt but enable a porous binder course to be used. It is available as a 10mm, 14mm or 20mm option.

Use this product for

• Tennis courts

Benefits

- Guaranteed drainage in accordance with LTA guidelines
- Meets SAPCA guidelines
- 100% recyclable

Also available with the following options: era®/CleanAir®/CarbonLock®

Please see asphalt product matrix for further information or contact technical:

northasphaltsales@uk.heidelbergmaterials.com southwestasphaltsales@uk.heidelbergmaterials.com southwalesasphaltsales@uk.heidelbergmaterials.com southeastasphaltsales@uk.heidelbergmaterials.com





DRAINAGE



INCLUDES RECYCLED CONTENT

