

## **Conformity Certificate**



## Regen Ground Granulated Blastfurnace Slag Produced at Sample Period

Port Talbot August 2022

## **Certificate of Conformity of Regen GGBS**

Spot samples of Regen GGBS were taken and tested to determine conformity to the autocontrol requirements of EN 15167-1 "Ground granulated blastfurnace slag for use in concrete, mortar and grout" following the methods given in that standard. The values reported are mean values for the monthly production period.

|   |  |                        | Result      | EN Limit   |
|---|--|------------------------|-------------|------------|
| Reger   | GGBS Only                                    |                        |             |            |
| Fineness m <sup>2</sup> /kg                                 |  |                        | 441         | min. 275   |
| Magnesia MgO %  |  |                        | 7           | max. 18    |
| Sulfate SO <sup>3</sup> %                                   |  |                        | 0.17        | max. 2.5   |
| Sulfide S <sup>2-</sup> %                                   |  |                        | 1.23        | max. 2.0   |
| Chloride Content Cl %                                       |  |                        | 0.07        | max. 0.1   |
| Moisture Content %  |  |                        | 0.07        | max. 1.0   |
| Aluminia Al <sub>2</sub> O <sub>3</sub> %                   |  |                        | 12          |            |
| Note: If the value is ≥ 14% the '+SR' restriction will be e | xceeded if the C <sub>3</sub> A of the CEM I | l is > 10 <sup>9</sup> | %.          |            |
| Alkalis as Na2  | O equ. (acid soluble)                        |                        |             |            |
| Certified Average Alkali (Last 25) %                        |  |                        | ≤ 1.0       |            |
| Mean Alkali content (Last 25) %                             |  |                        | 0.75        |            |
| Declared Mean: Mean last 25 + (SD last 25 x 1.64) %         |  |                        | 0.81        |            |
| Combination of 50% Laboratory Stock                         | CEM I Portland Cement and 5                  | 0% Reg                 | en GGBS     |            |
| Initial Setting Time min.                                   |  |                        | 189         | > 2 x PC   |
| Activity Index %  | 7  | days                   | 68          | min. 45    |
|   | 28   | 8 days                 | 87          | min. 70    |
| Laboratory Stock C  | EM I Portland Cement Only                    |                        |             |            |
| The laboratory stock CEM I Portland cem                     | ent used in these tests was sup              | plied by               | Hanson.     |            |
| Initial Setting Time min                                    |  |                        | 139         |            |
| Compressive Strength N/mm <sup>2</sup>                      | 7  | days                   | 47.6        |            |
|   | 28   | 8 days                 | 60.6        |            |
| The Regen GGBS contained no additional materials of         |  | •                      | eulte and o | ther tests |

demonstrate the conformity of the material sold during the month to the requirements of EN 15167-1.

Hanson Cement has used all reasonable care to ensure the information herein contained is accurate but to the extent permitted in law, no liability can be accepted by Hanson Cement for any loss, damage, cost or expense arising from any inaccuracy, whether due to negligence or otherwise.

Signed:

10 Cerdial

Dr Nina Cardinal, Dipl.Ing., CEng, MiMMM National Technical Manager

CF CK

1333-CPR-00134