Castle Cement Ltd T/A Hanson Cement, Hanson House, 14 Castle Hill, Maidenhead, Berkshire, SL6 4JJ **Ribblesdale Works** 1333-CPR-00248





## **Cement Test Report**

Hanson Cement Ketton Stamford PE9 3SX Tel: 0330 123 2074 Fax: 01780 727008

Results of tests made at the laboratories of the company on samples of

Ribblesdale PLC 52,5N, BS EN 197-1:2011 - CEM II/A-LL 52,5N Dispatched from Ribblesdale during week ending

and during week ending

10-Jul-22 (Week No. 2022-27 ) 19-Jun-22 (Week No. 2022-24 ) for 28 day results

| Date      | Fineness                       | Setting Time | Soundness | Compressive Strength              |                      |                      | Chloride | Alkali                      |           |
|-----------|--------------------------------|--------------|-----------|-----------------------------------|----------------------|----------------------|----------|-----------------------------|-----------|
|           | Specific<br>Surface<br>(m²/kg) | Initial      | Expansion | 40mm x 40mm x 160mm Mortar prisms |                      |                      |          | Certified<br>Average Alkali | Standard  |
|           |                                | (mins)       | (mm)      | 2 Days                            | 7 Days               | 28 Days              | %        | % Na <sub>2</sub> O eq      | Deviation |
|           |                                |              |           | (N/mm <sup>2</sup> )              | (N/mm <sup>2</sup> ) | (N/mm <sup>2</sup> ) |          |                             |           |
| 04-Jul-22 | 440                            | 155          | 1         | 37.5                              | 51.0                 |                      | 0.06     | 0.70                        | 0.03      |
| 08-Jul-22 | 465                            | 160          | 1         | 33.0                              | 43.5                 |                      | 0.06     | 0.70                        | 0.03      |
| Average   | 455                            | 160          | 1         | 35.5                              | 47.5                 |                      | 0.06     |                             | 0.03      |
| 13-Jun-22 | 485                            | 180          | 1         | 36.0                              | 48.5                 | 59.5                 | 0.06     | 0.69                        | 0.03      |
| 17-Jun-22 | 480                            | 170          | 1         | 36.0                              | 48.5                 | 58.0                 | 0.06     | 0.69                        | 0.03      |
| Average   | 485                            | 175          | 1         | 36.0                              | 48.5                 | 59.0                 | 0.06     |                             | 0.03      |

Product Declaration:

Declared Mean Alkali (%) = 0.75 (Max) Declared Chloride content (%) = 0.07 (Max)

For and on behalf of HANSON CEMENT

1) Cerdial

Dr Nina Cardinal, Dipl.Ing., CEng, MiMMM National Technical Manager Hanson Cement

Hanson Cement has used all reasonable care to ensure the information herein contained is accurate but to the extent permitted in law, no liability can be accepted by Hanson Cement for any loss, damage, cost or expense arising from any inaccuracy, whether due to negligence or otherwise.

Registered Office: Hanson House, 14 Castle Hill, Maidenhead, Berkshire, SL6 4JJ Registered in England No. 2182762